

LAKELAND *paints*

PRODUCT ADVICE

LAKELAND BLACKBOARD-CHALKBOARD PAINT

LAKELAND paints offer a completely unique range of decorative finishes. It's the only range of totally solvent-free paints available anywhere in the world today, independently tested to reveal 0.0% VOCs (Volatile Organic Compounds).

VOCs are a major contributor to low-level atmospheric pollution and the use of these compounds leads to global warming. In addition, the use of solvent-based paints is a major cause of, asthma, allergies, sick building syndrome, chemical sensitivities and the general flu-like symptoms reported by many people using conventional paints, including Matt and Silk wall paints.

Most paints currently on sale, both gloss and emulsion, contain solvents and VOCs. LAKELAND paints contain none.

As a result they are ideal for use throughout the home, particularly children's bedrooms, nurseries and kitchens, especially if you or a member of your family is chemically sensitive or suffers from asthma or allergies.

Where to use:

Solid interior walls, doors, or purpose-built chalkboards & blackboard panels.

LAKELAND Chalkboard - Blackboard Paint is a hard, washable, super-resilient paint designed for creating your own chalkboards, blackboards and chalkboard surfaces. The super-matt finish ideally takes all general purpose and pavement chalks and is fully washable.

Availability:

In 1 and 5 litre tins in all 180 LAKELAND colours plus white. Available direct from Lakeland Paints.

Coverage: 50m² per 5 litre/per coat depending on surface porosity

Drying time: Touch dry in 1 – 2 hours. Recoat after minimum 6 hours.

Sheen level: 9%

Preparation:

Surfaces should be clean, dry, sound and free from grease. If in doubt clean with sugar soap and rinse well. Remove all soft, dusty and loose material and abrade lightly. Bare wood should be primed first with LAKELAND Wood Primer. Can be used on Hard plaster surfaces – bare plaster should first be sealed with LAKELAND Plaster Sealer.

Application:

Lakeland Paints, Unit 19, Heysham Business Park, Middleton Road, Heysham, LA3 3PP
01524 852371 www.lakelandpaints.co.uk

DO NOT THIN. Stir gently and thoroughly before use. Apply where possible by narrow (6-7 inch) foam or fine pile "gloss" roller. Do not layoff. Do not go back over painted areas. Do not over spread. Can be sprayed using an airless spray system. Best results are normally achieved with two coats. Allow minimum six hours between coats. Avoid applying below 5C and above 25c. Normally touch dry in 1-2 hours. Clean equipment promptly with water.

Important Notes:

Once thoroughly hard, after at least 7 days, wipe over with the side of a chalk stick, then wipe clean. Your chalkboard is now ready for years of use! To prevent inhalation of chalk dust, it is always advisable to use a damp cloth to clean your chalkboard.

Maintenance:

Remove chalk with a damp cloth. Other marks - use a mild detergent & water. Do not use harsh, abrasive or alkaline cleaners.

Storage:

This product is water based and must be protected from frost and extreme temperatures. Use within 12 months of purchase. We accept no responsibility for the deterioration of contents or packaging after this.

Disposal:

Though water based, please do not dispose of into watercourses. Waste materials must be disposed of in accordance with the Environmental Protection Act 1990 and relevant regulations made there under. For further information contact the Environment Office at your local council.

Health & Safety:

Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water. After contact with skin wash off with water. Keep out of reach of children

Safety Data Sheets are available on request.