

LAKELAND *paints*

PRODUCT ADVICE

LAKELAND STAIN BLOCK

LAKELAND paints offer a completely unique range of decorative finishes. It's the only range of totally solvent-free paints available anywhere in the world today, independently tested to reveal 0.0% VOCs (Volatile Compounds).

VOCs are a major contributor to low-level atmospheric pollution and the use of these compounds leads to global warming. In addition, the use of solvent-based paints is a major cause of, asthma, allergies, sick building syndrome, chemical sensitivities and the general flu-like symptoms reported by many people using conventional paints, including Matt and Silk wall paints.

Most paints currently on sale, both gloss and emulsion, contain solvents and VOCs. LAKELAND paints contain none.

As a result they are ideal for use throughout the home, particularly children's bedrooms, nurseries and kitchens, especially if you or a member of your family is chemically sensitive or suffers from asthma or allergies.

Where to use:

This water based, solvent-free stainblock is highly effective & has a number of uses for concealing & blocking out difficult stains such as rusted metal, rust staining, tannin staining from hardwoods such as oak and mahogany, water staining on plaster walls & ceilings from leaking roofs, gutters, cisterns, & many other difficult to remove stains. This product will not block oily or tarry stains such as those from coal fires (chimney breast) or asphalt. Not ideal for exterior bare cast iron - ask for advice. This is the preferred Primer for bare Iron & Steel. Not for aviaries - Stainblock contains zinc oxide.

Availability:

In 1 and 5 litre tins. Available direct from Lakeland Paints.

Coverage: 10-12m² per litre/per coat (depending on surface porosity)

Drying time: Touch dry in 1 – 2 hours, recoat in 6 hours

Sheen level: 6%

Preparation:

The substrate should be sound, DRY, non-dusty, non-oily. Remove any loose or flaking material. Structural issues such as efflorescence, water ingress or rising damp, etc, must be resolved beforehand & re-plastered if needs be. Metals - rust must be removed.

Painting:

Do not paint in direct sunshine or temperatures below 5°C or above 25°C.

Lakeland Paints, Unit 19, Heysham Business Park, Middleton Road, Heysham, LA3 3PP
01524 852371 www.lakelandpaints.co.uk

Stir gently & thoroughly before use. Apply 2 or 3 thin even coats by brush or roller - depending on the severity of the problem - allow at least 6 hrs between coats. The final coat should be pure white before recoating. DILUTE WITH A LITTLE WATER ONLY IF NECESSARY. Finish with any of our standard wall or trim paints - if in doubt, ask for advice

Clean up:

Clean brushes and rollers with warm soapy water.

Storage:

This product is water based and must be protected from frost and extreme temperatures. Use within 4 months of purchase. We accept no responsibility for the deterioration of contents or packaging after this.

Disposal:

Though water based, please do not dispose of into watercourses. Waste materials must be disposed of in accordance with the Environmental Protection Act 1990 and relevant regulations made there under. For further information contact the Environment Office at your local council.

Health & Safety:

Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water. After contact with skin wash off with water. Keep out of reach of children.

Safety Data Sheets are available on request.