

# LAKELAND *paints*

## PRODUCT ADVICE

### LAKELAND ANTI-FORMALDEHYDE RADIATOR PAINT

LAKELAND paints offer a completely unique range of decorative finishes. It's the only range of totally solvent-free paints available anywhere in the world today, independently tested to reveal 0.0% VOCs (Volatile Organic Compounds).

VOCs are a major contributor to low-level atmospheric pollution and the use of these compounds leads to global warming. In addition, the use of solvent-based paints is a major cause of, asthma, allergies, sick building syndrome, chemical sensitivities and the general flu-like symptoms reported by many people using conventional paints, including Matt and Silk wall paints.

Most paints currently on sale, both gloss and emulsion, contain solvents and VOCs. LAKELAND paints contain none.

As a result they are ideal for use throughout the home, particularly children's bedrooms, nurseries and kitchens, especially if you or a member of your family is chemically sensitive or suffers from asthma or allergies.

Where to use:

Previously painted or primed domestic central heating radiators.(Electric, storage or steam radiators etc. ask for advice). Not suitable for bare copper.

Conventional central heating radiators can offgas large amounts of formaldehyde\*. The special silicate ingredients in LAKELAND AFR paint absorbs approx. 98-99% formaldehyde down to around 1ppm, before it can offgas into your home environment. Available in matt white, this AFR base coat is best finished with LAKELAND Feng Shui if a coloured finish is required.

Availability:

In 1 and 5 litre tins in white. Available direct from Lakeland Paints.

Coverage: 10m<sup>2</sup> per litre/per coat

Drying time: Touch dry in 1 to 2 hours. Recoat after minimum 8 hours.

Sheen level: 15%

Preparation:

Surfaces should be cold, clean, dry and free from rust, grease and polish residues. If in doubt clean with detergent or sugarsoap and Scotchbrite plastic scouring pad. Rinse and dry thoroughly. All bare metal should ideally be primed with two thin coats of LAKELAND Stainblock.

Note: Bare cast iron or blast-cleaned radiators-ask for advice.

Lakeland Paints, Unit 19, Heysham Business Park, Middleton Road, Heysham, LA3 3PP  
01524 852371 [www.lakelandpaints.co.uk](http://www.lakelandpaints.co.uk)

#### Painting:

Stir gently and thoroughly before use. Use best quality soft paint brushes. Work progressively along the radiator. Best results are normally achieved with two medium coats.

**IMPORTANT:** Do not over - brush. Do not layoff. Do not go back over painted areas. Do not thin. Paint only onto cold radiators - do not force-dry. Radiators can be put back into service only when the paint film is dry.

Overcoating - if a coloured finish is required, finish with Lakeland Satin-Gloss or Feng Shui systems.

#### Storage:

This product is water based and must be protected from frost and extreme temperatures. Use within 6 months of purchase. We accept no responsibility for the deterioration of contents or packaging after this.

#### Disposal:

Though water based, please do not dispose of into watercourses. Waste materials must be disposed of in accordance with the Environmental Protection Act 1990 and relevant regulations made there under. For further information contact the Environment Office at your local council.

#### Health & Safety:

Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water. After contact with skin wash off with water. Keep out of reach of children. Safety Data Sheets are available on request.

Safety Data Sheets are available on request.