

LAKELAND *paints*

PRODUCT ADVICE

LAKELAND ANTI-SLIP FLOOR PAINT

LAKELAND paints offer a completely unique range of decorative finishes. It's the only range of totally solvent-free paints available anywhere in the world today, independently tested to reveal 0.0% VOCs (Volatile Organic Compounds).

VOCs are a major contributor to low-level atmospheric pollution and the use of these compounds leads to global warming. In addition, the use of solvent-based paints is a major cause of, asthma, allergies, sick building syndrome, chemical sensitivities and the general flu-like symptoms reported by many people using conventional paints, including Matt and Silk wall paints.

Most paints currently on sale, both gloss and emulsion, contain solvents and VOCs. LAKELAND paints contain none.

As a result they are ideal for use throughout the home, particularly children's bedrooms, nurseries and kitchens, especially if you or a member of your family is chemically sensitive or suffers from asthma or allergies.

Where to use:

Interior - wooden floors (not teak or oily woods) & dry concrete floors (not subject to ponding).
Hardwoods – ask for advice.

Availability:

In 5 litre tins in all 180 LAKELAND colours plus white. Colour matching available upon request.
Available direct from Lakeland Organic Paints.

Coverage: Up to 50m² per 5 litres/per coat

Drying time: Touch dry in 1 – 2 hours, recoat in 24 hours

Preparation:

Wooden floors - Ensure the surface is sound, dry and free of dust, wax, & grease. For best results clean with a Scotchbrite pad & detergent. This product is suitable for direct application onto bare wood. Fillers - seal with Lakeland Filler Sealer. Knots - treat with two coats of Lakeland White Knotting. Bare concrete floors must be dry, non-dusty & free of laitance & contaminants. Previously painted floors must be clean, dry & free of loose or flaking paint & free of polish/wax residues - if in doubt clean with a Scotchbrite pad & sugar soap & rinse well. Lakeland Floor Paint will key to most finishes, but a test area is always advisable. Remove dust with a Tak rag.

Painting:

Lakeland Paints, Unit 19, Heysham Business Park, Middleton Road, Heysham, LA3 3PP
01524 852371 www.lakelandpaints.co.uk

Stir thoroughly & gently before use & occasionally during use. On bare concrete, the first coat can be diluted by the addition of 10% water to help adhesion. Apply with a 6-10" Gloss Paint or Foam roller; do not over-spread.

Floorboards – work along the length, not across. Two coats normally needed.

IMPORTANT – do not lay-off, do not go back over wet painted areas, for best results allow to dry at least overnight before recoating. Touch dry in 1-2 hrs. When touch-dry the floor can be walked on (with care), but avoid scraping, scuffing or wetting for 10 days - when ultimate hardness is achieved. Do not apply below 5 deg C or above 25 deg C or in direct sunlight.

Maintenance:

Clean with a damp cloth using dilute mild detergent. Do not use harsh, abrasive or alkaline cleaners. Do not allow ponding. Do not use floor waxes or other treatments.

Clean up:

Clean brushes and rollers with warm soapy water.

Cleaning:

Wipe gently with a soft damp cloth or sponge.

Storage:

This product is water based and must be protected from frost and extreme temperatures. Use within 12 months of purchase. We accept no responsibility for the deterioration of contents or packaging after this.

Disposal:

Though water based, please do not dispose of into watercourses. Waste materials must be disposed of in accordance with the Environmental Protection Act 1990 and relevant regulations made there under. For further information contact the Environment Office at your local council.

Health & Safety:

Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water. After contact with skin wash off with water. Keep out of reach of children. Safety Data Sheets are available on request.

Safety Data Sheets are available on request.