

LAKELAND *paints*

PRODUCT ADVICE

LAKELAND SATIN GLOSS

LAKELAND paints offer a completely unique range of decorative finishes. It's the only range of totally solvent-free paints available anywhere in the world today, independently tested to reveal 0.0% VOCs (Volatile Compounds).

VOCs are a major contributor to low-level atmospheric pollution and the use of these compounds leads to global warming. In addition, the use of solvent-based paints is a major cause of, asthma, allergies, sick building syndrome, chemical sensitivities and the general flu-like symptoms reported by many people using conventional paints, including Matt and Silk wall paints.

Most paints currently on sale, both gloss and emulsion, contain solvents and VOCs. LAKELAND paints contain none.

As a result they are ideal for use throughout the home, particularly children's bedrooms, nurseries and kitchens, especially if you or a member of your family is chemically sensitive or suffers from asthma or allergies.

Where to use:

Interior woodwork and suitably primed or previously painted metal.

Availability:

In 1 and 5 litre tins in all 180 LAKELAND colours plus white. Colour matching available upon request. Available direct from Lakeland Paints.

Coverage: 10m² per litre/per coat

Drying time: Touch dry in 1 – 2 hours, recoat in 24 hours

Sheen level: 21%

Preparation:

Surfaces should be sound, clean, dry and free from grease. Lightly abrade previously painted surfaces with a wet scotchbrite pad & dry.

Painting:

Do not paint in direct sunlight or temperatures below 5°C or above 25°C.

Please check for colour accuracy prior to use as we will not be liable for decorating caused as a result of an incorrect colour being applied.

Stir gently & thoroughly before use. Apply generously with a well loaded brush.

Lakeland Paints, Unit 19, Heysham Business Park, Middleton Road, Heysham, LA3 3PP
01524 852371 www.lakelandpaints.co.uk

Bare wood - ensure the surface is smooth and dust free; best results are achieved with one coat of LAKELAND Primer followed by one coat of LAKELAND Undercoat and two coats of LAKELAND Satin.

Bare Hardwoods – contact Lakeland Paints for further advice.

Knots - treat with two coats of LAKELAND White Knotting.

Fillers - seal with LAKELAND Filler Sealer.

Bare iron and steel - prepare with LAKELAND Stainblock.

NOTE: our satinwood may be incompatible with other primers and undercoats.

IMPORTANT: use best quality soft paint brushes - work progressively along, do not overbrush, do not lay off, do not go back over painted areas: do not thin: Allow to dry at least over night (and preferably 24 hours) between coats. Clean equipment with water.

APPLICATION HINTS: Panelled doors are best painted in sections e.g. panels, then rails, then stiles. Large flat areas (eg plain doors) are best painted with a gloss roller. Remove door furniture. Hardening continues for approx 7 - 10 days; avoid wetting & scuffing for this period.

Clean up:

Clean brushes and rollers with warm soapy water.

Cleaning:

Wipe gently with a soft damp cloth or sponge. Do not use harsh, abrasive or alkaline cleansers.

Storage:

This product is water based and must be protected from frost and extreme temperatures. Use within 12 months of purchase. We accept no responsibility for the deterioration of contents or packaging after this.

Disposal:

Though water based, please do not dispose of into watercourses. Waste materials must be disposed of in accordance with the Environmental Protection Act 1990 and relevant regulations made there under. For further information contact the Environment Office at your local council.

Health & Safety:

Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water. After contact with skin wash off with water. Keep out of reach of children.

Safety Data Sheets are available on request.