

# LAKELAND *paints*

## PRODUCT ADVICE

### LAKELAND STONE & TILE FLOOR SEALER

LAKELAND paints offer a completely unique range of decorative finishes. It's the only range of totally solvent-free paints available anywhere in the world today, independently tested to reveal 0.0% VOCs (Volatile Compounds).

VOCs are a major contributor to low-level atmospheric pollution and the use of these compounds leads to global warming. In addition, the use of solvent-based paints is a major cause of, asthma, allergies, sick building syndrome, chemical sensitivities and the general flu-like symptoms reported by many people using conventional paints, including Matt and Silk wall paints.

Most paints currently on sale, both gloss and emulsion, contain solvents and VOCs. LAKELAND paints contain none.

As a result they are ideal for use throughout the home, particularly children's bedrooms, nurseries and kitchens, especially if you or a member of your family is chemically sensitive or suffers from asthma or allergies.

Where to use:

Plain and rough stone & unglazed tiles including terracotta, slate, limestone, marble, sandstone, reconstituted stones & tiles etc and also the cement /grout used in-between. Not ideally suited to polished granite or similar.

This odourless, solvent free sealer offers unrivalled protection for plain or rough stone & tile floors, worktops, splashbacks & other stone & tile surfaces as it does not noticeably change the appearance or colour of the surface once dry & has no shine. It sheds water & mud & protects against most food stains including tea, coffee, red wine, cordial, blackcurrant & other fruit juices, milk, sauces, curry, ketchup, etc. Note: It offers only minimal protection against oily/greasy stains. It is entirely non-toxic.

Availability:

In 1 and 5 litre plastic containers. Available direct from Lakeland Paints.

Coverage: Varies considerably with the porosity of the substrate, but is normally in the range 5 m<sup>2</sup>/L/coat - (for terracotta, sandstone, or similar) to 14m<sup>2</sup>/ L /coat -(for slate, marble, limestone etc). These figures are for guidance only.

Drying time: 1 – 2 hours (depending on ventilation)

Preparation:

Lakeland Paints, Unit 19, Heysham Business Park, Middleton Road, Heysham, LA3 3PP  
01524 852371 [www.lakelandpaints.co.uk](http://www.lakelandpaints.co.uk)

Ensure the surface is sound, dry, non-dusty, non-greasy. If in doubt as to the suitability of this product, a test area on scrap or spare tile/stone is highly recommended.

**Application:**

Shake or stir before use. Apply one thin coat by spray, brush, roller, squeegee or sponge - depending on the porosity of the substrate. Do not allow ponding of the product. Remove any surface residual liquid straight away with a sponge or cloth.

**Clean up:**

Clean brushes and rollers with warm soapy water.

**Storage:**

This product is water based and must be protected from frost and extreme temperatures. Use within 12 months of purchase. We accept no responsibility for the deterioration of contents or packaging after this.

**Disposal:**

Though water based, please do not dispose of into watercourses. Waste materials must be disposed of in accordance with the Environmental Protection Act 1990 and relevant regulations made there under. For further information contact the Environment Office at your local council.

**Health & Safety:**

Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water. After contact with skin wash off with water. Keep out of reach of children.

Safety Data Sheets are available on request.