

# LAKELAND *paints*

## PRODUCT ADVICE

### LAKELAND SUPER CHALKY DESIGNER WALLPAINT

LAKELAND paints offer a completely unique range of decorative finishes. It's the only range of totally solvent-free paints available anywhere in the world today, independently tested to reveal 0.0% VOCs (Volatile Compounds).

VOCs are a major contributor to low-level atmospheric pollution and the use of these compounds leads to global warming. In addition, the use of solvent-based paints is a major cause of, asthma, allergies, sick building syndrome, chemical sensitivities and the general flu-like symptoms reported by many people using conventional paints, including Matt and Silk wall paints.

Most paints currently on sale, both gloss and emulsion, contain solvents and VOCs. LAKELAND paints contain none.

As a result they are ideal for use throughout the home, particularly children's bedrooms, nurseries and kitchens, especially if you or a member of your family is chemically sensitive or suffers from asthma or allergies.

#### Availability:

In 5 litre tins in all 180 Lakeland colours plus white. Colour matching available upon request. Available direct from Lakeland Paints.

#### Description:

Highly durable, non-dusting, wipeable and super-breathable paint. The ultra matt finish gives a very pleasant impression of evenness, softness and enhanced appearance similar to suede or vellum. Ideal for corridors, hallways & where a super-matt finish is needed or desirable.

#### Usage:

A high quality emulsion designed for use throughout the house on ceilings and walls. Not ideal for areas subject to very frequent wetting. For constantly wetted areas such as kitchens and bathrooms, consider Lakeland Eggshell Wallpaint or FengShui Multi Surface Paint.

Coverage: Up to 50 m<sup>2</sup> per 5 litres/per coat

Drying time: Touch dry in 1 to 2 hours, recoat in 4 hours

Sheen level: <3%

#### Preparation:

Ensure surfaces are sound, clean, dry and free from dirt, grease and other contamination.

#### Painting:

Lakeland Paints, Unit 19, Heysham Business Park, Middleton Road, Heysham, LA3 3PP  
01524 852371 [www.lakelandpaints.co.uk](http://www.lakelandpaints.co.uk)

Do not paint in direct sunshine or temperatures below 5°C or above 25°C.

Please check for colour accuracy prior to use as we will not be liable for decorating caused as a result of an incorrect colour being applied. When more than one tin of the same colour is to be used ensure that they are intermixed before use. Stir thoroughly before use.

Apply two coats using a medium pile roller. Always lay off in one direction.

Useful application hints - this traditional formulation has a greater porosity than standard emulsions.

Airless Spraying – Good results can be achieved by the set up of 18 thou 65° angle tip using a pressure of between 2000 - 2700 psi.

Clean up:

Clean brushes and rollers with warm soapy water.

Cleaning:

Wipe gently with a soft damp cloth or sponge.

Storage:

This product is water based and must be protected from frost and extreme temperatures. Use within 12 months of purchase. We accept no responsibility for the deterioration of contents or packaging after this.

Disposal:

Though water based, please do not dispose of into watercourses. Waste materials must be disposed of in accordance with the Environmental Protection Act 1990 and relevant regulations made there under. For further information contact the Environment Office at your local council.

Health & Safety:

Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water. After contact with skin wash off with water. Keep out of reach of children.

Safety Data Sheets are available on request.