

# LAKELAND *paints*

## PRODUCT ADVICE

### LAKELAND WOOD GLUE

LAKELAND paints offer a completely unique range of decorative finishes. It's the only range of totally solvent-free paints available anywhere in the world today, independently tested to reveal 0.0% VOCs (Volatile Compounds).

VOCs are a major contributor to low-level atmospheric pollution and the use of these compounds leads to global warming. In addition, the use of solvent-based paints is a major cause of, asthma, allergies, sick building syndrome, chemical sensitivities and the general flu-like symptoms reported by many people using conventional paints, including Matt and Silk wall paints.

Most paints currently on sale, both gloss and emulsion, contain solvents and VOCs. LAKELAND paints contain none.

As a result they are ideal for use throughout the home, particularly children's bedrooms, nurseries and kitchens, especially if you or a member of your family is chemically sensitive or suffers from asthma or allergies.

#### Where to use:

Interior woodwork, joinery, wooden floor tiles & laminates, floorboards, cork sheeting & tiles etc. Can also be used for paper, card, carpet, fabric, etc. Not suitable for teak or other oily woods or asphalt-sealed surfaces. Can be used on unsealed chipboard, hardboard, non-dusty cement screed & concrete substrates.

#### Availability:

In 1 and 5 litre tins. Available direct from Lakeland Paints.

Coverage: around 20m<sup>2</sup> per 5 litres, depending on surface porosity

#### Preparation:

Ensure that the surfaces to be joined are clean, dry, non-dusty & free of oil & wax. Previously varnished surfaces can also often be joined, but a thorough rub down with emery/glass paper is essential & a test area is advised. Dusty concrete/cement floors may need to be sealed: ask for advice.

#### Application:

Flooring - best applied to the substrate with a notching tool - (ideally approx. 3mm at 10mm centres) - once spread, the adhesive should remain "wet" & workable for approx. 20 mins, but this does depend in part on the absorbency of the materials involved - if in doubt, a test area is advised - Only cover an area which can be finished within this timeframe. Press the floorcovering firmly into place. Remove traces of wet adhesive with a damp cloth. Avoid use in temperatures below 5 & above 25 degrees centigrade or in direct sunlight.

Lakeland Paints, Unit 19, Heysham Business Park, Middleton Road, Heysham, LA3 3PP  
01524 852371 [www.lakelandpaints.co.uk](http://www.lakelandpaints.co.uk)

Joinery - use as normal, apply with a brush or knife/spatula; preferably clamp until hard dry (min. 8 hrs). Remove excess with a damp cloth.

**Storage:**

This product is water based and must be protected from frost and extreme temperatures. Use within 12 months of purchase. We accept no responsibility for the deterioration of contents or packaging after this.

**Disposal:**

Though water based, please do not dispose of into watercourses. Waste materials must be disposed of in accordance with the Environmental Protection Act 1990 and relevant regulations made there under. For further information contact the Environment Office at your local council.

**Health & Safety:**

Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water. After contact with skin wash off with water. Keep out of reach of children.

Safety Data Sheets are available on request.